

PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
  
PAS  
  
PAS  
  
PAS  
PAS  
PAS  
PAS  
PAS  
  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS  
PAS

[illegible]

(2) 46  
(3) 75  
(4) 114  
(5) 153  
(6) 192

DECLARATIONS  
PASSEXPO\_F - Return binary exponent of F\_floating  
PASSEXPO\_D - Return binary exponent of D\_floating  
PASSEXPO\_G - Return binary exponent of G\_floating  
PASSEXPO\_H - Return binary exponent of H\_floating

```
0000 1 .TITLE PASSEXPO - Return binary exponent of floating values
0000 2 .IDENT /1-001/ ; File: PASEXPO.MAR Edit: SBL1001
0000 3
0000 4
0000 5 :*****
0000 6 :*
0000 7 :* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8 :* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9 :* ALL RIGHTS RESERVED.
0000 10 :*
0000 11 :* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12 :* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13 :* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14 :* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15 :* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16 :* TRANSFERRED.
0000 17 :*
0000 18 :* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19 :* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20 :* CORPORATION.
0000 21 :*
0000 22 :* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23 :* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24 :*
0000 25 :*
0000 26 :*****
0000 27 :
0000 28
0000 29 :++
0000 30 : FACILITY: Pascal Language Support
0000 31 :
0000 32 : ABSTRACT:
0000 33 :
0000 34 : This module contains four routines which return the binary exponent
0000 35 : of a floating value for each of the four floating data types.
0000 36 :
0000 37 : ENVIRONMENT: Runs at any access mode, AST Reentrant
0000 38 :
0000 39 : AUTHOR: Steven B. Lionel, CREATION DATE: 4-Nov-1980
0000 40 :
0000 41 : MODIFIED BY:
0000 42 :
0000 43 : 1-001 - Original. SBL 4-Nov-1980
0000 44 :--
```

```
0000 46 .SBTTL DECLARATIONS
0000 47 :
0000 48 : LIBRARY MACRO CALLS:
0000 49 :
0000 50 : NONE
0000 51 :
0000 52 : EXTERNAL DECLARATIONS:
0000 53 :
0000 54 : .DSABL GBL ; Force all external symbols to be declared
0000 55 : NONE
0000 56 :
0000 57 : MACROS:
0000 58 :
0000 59 : NONE
0000 60 :
0000 61 : EQUATED SYMBOLS:
0000 62 :
0000 63 : NONE
0000 64 :
0000 65 : OWN STORAGE:
0000 66 :
0000 67 : NONE
0000 68 :
0000 69 : PSECT DECLARATIONS:
0000 70 :
00000000 71 : .PSECT _PASS$CODE PIC, USR, CON, REL, LCL, SHR, -
0000 72 : EXE, RD, NOWRT, LONG
0000 73 :
```

```
0000 75 .SBTTL PASSEXPO_F - Return binary exponent of F_floating
0000 76 :++
0000 77 : FUNCTIONAL DESCRIPTION:
0000 78 :
0000 79 : This routine returns the unbiased binary exponent of an F_floating value.
0000 80 :
0000 81 : CALLING SEQUENCE:
0000 82 :
0000 83 : Result.wl.v = PASSEXPO_F (Single.rf.r)
0000 84 :
0000 85 : FORMAL PARAMETERS:
0000 86 :
0000 87 : Single - F_floating argument
0000 88 :
0000 89 : IMPLICIT INPUTS:
0000 90 :
0000 91 : NONE
0000 92 :
0000 93 : IMPLICIT OUTPUTS:
0000 94 :
0000 95 : NONE
0000 96 :
0000 97 : ROUTINE VALUE:
0000 98 :
0000 99 : The unbiased binary exponent of the argument
0000 100 :
0000 101 : SIDE EFFECTS:
0000 102 :
0000 103 : SS$_ROPRAND - if the argument is a reserved operand
0000 104 :
0000 105 :--
0000 106 :
0000 107 .ENTRY PASSEXPO_F, ^M<> ; Entry point
0002 108
0002 109 TSTF @4(AP) ; Test for reserved operand
50 04 BC 04 BC 53 0002 110 EXTZV #7, #8, @4(AP), R0 ; Fetch exponent
50 00000080 8F EF 0005 111 SUBL2 #128, R0 ; Unbias exponent
04 0012 112 RET ; End of routine PASSEXPO_F
```

```
0013 114 .SBTTL PASSEXPO_D - Return binary exponent of D_floating
0013 115 :++
0013 116 : FUNCTIONAL DESCRIPTION:
0013 117 :
0013 118 : This routine returns the unbiased binary exponent of a D_floating value.
0013 119 :
0013 120 : CALLING SEQUENCE:
0013 121 :
0013 122 : Result.wl.v = PASSEXPO_D (Double.rd.r)
0013 123 :
0013 124 : FORMAL PARAMETERS:
0013 125 :
0013 126 : Double - D_floating argument
0013 127 :
0013 128 : IMPLICIT INPUTS:
0013 129 :
0013 130 : NONE
0013 131 :
0013 132 : IMPLICIT OUTPUTS:
0013 133 :
0013 134 : NONE
0013 135 :
0013 136 : ROUTINE VALUE:
0013 137 :
0013 138 : The unbiased binary exponent of the argument
0013 139 :
0013 140 : SIDE EFFECTS:
0013 141 :
0013 142 : $$$_ROPRAND - if the argument is a reserved operand
0013 143 :
0013 144 :--
0000 0013 145
0013 146 .ENTRY PASSEXPO_D, ^M<> ; Entry point
0015 147
0015 148 TSTD @4(AP) ; Test for reserved operand
0018 149 EXTZV #7, #8, @4(AP), R0 ; Fetch exponent
001E 150 SUBL2 #128, R0 ; Unbias exponent
0025 151 RET ; End of routine PASSEXPO_D
```

50 04 BC 08 07 EF 0015 148  
50 00000080 8F C2 001E 150  
04 0025 151

```
0026 153 .SBTTL PASSEXPO_G - Return binary exponent of G_floating
0026 154 :++
0026 155 : FUNCTIONAL DESCRIPTION:
0026 156 :
0026 157 : This routine returns the unbiased binary exponent of a G_floating value.
0026 158 :
0026 159 : CALLING SEQUENCE:
0026 160 :
0026 161 : Result.wl.v = PASSEXPO_G (Double.rg.r)
0026 162 :
0026 163 : FORMAL PARAMETERS:
0026 164 :
0026 165 : Double - G_floating argument
0026 166 :
0026 167 : IMPLICIT INPUTS:
0026 168 :
0026 169 : NONE
0026 170 :
0026 171 : IMPLICIT OUTPUTS:
0026 172 :
0026 173 : NONE
0026 174 :
0026 175 : ROUTINE VALUE:
0026 176 :
0026 177 : The unbiased binary exponent of the argument
0026 178 :
0026 179 : SIDE EFFECTS:
0026 180 :
0026 181 : $$$_ROPRAND - if the argument is a reserved operand
0026 182 :
0026 183 :--
0026 184 :
0000 0026 185 .ENTRY PASSEXPO_G, ^M<> ; Entry point
0028 186
50 04 BC 04 BC 53FD 0028 187 TSTG @4(AP) ; Test for reserved operand
50 04 BC 0B 04 EF 002C 188 EXTZV #4, #11, @4(AP), R0 ; Fetch exponent
50 00000400 8F C2 0032 189 SUBL2 #1024, R0 ; Unbias exponent
04 0039 190 RET ; End of routine PASSEXPO_G
```

```
003A 192 .SBTTL PASSEXPO_H - Return binary exponent of H_floating
003A 193 :++
003A 194 : FUNCTIONAL DESCRIPTION:
003A 195 :
003A 196 :     This routine returns the unbiased binary exponent of an H_floating value.
003A 197 :
003A 198 : CALLING SEQUENCE:
003A 199 :
003A 200 :     Result.wl.v = PASSEXPO_H (Quad.rh.r)
003A 201 :
003A 202 : FORMAL PARAMETERS:
003A 203 :
003A 204 :     Quad    - H_floating argument
003A 205 :
003A 206 : IMPLICIT INPUTS:
003A 207 :
003A 208 :     NONE
003A 209 :
003A 210 : IMPLICIT OUTPUTS:
003A 211 :
003A 212 :     NONE
003A 213 :
003A 214 : ROUTINE VALUE:
003A 215 :
003A 216 :     The unbiased binary exponent of the argument
003A 217 :
003A 218 : SIDE EFFECTS:
003A 219 :
003A 220 :     $$$_ROPRAND - if the argument is a reserved operand
003A 221 :
003A 222 :--
003A 223 :
0000 003A 224 .ENTRY PASSEXPO_H, ^M<> ; Entry point
003C 225
50 04 BC 0F 00 EF 003C 226 TSTH @4(AP) ; Test for reserved operand
50 04 BC 0F 00 EF 0040 227 EXTZV #0, #15, @4(AP), R0 ; Fetch exponent
50 00004000 8F C2 0046 228 SUBL2 #16384, R0 ; Unbias exponent
04 004D 229 RET ; End of routine PASSEXPO_H
004E 230
004E 231 .END ; End of module PASSEXPO
```

PASSEXPO  
Symbol table

- Return binary exponent of floating val 16-SEP-1984 01:24:54 VAX/VMS Macro V04-00  
6-SEP-1984 11:30:34 [PASRTL.SRC]PASEXPO.MAR;1

Page 7  
(6)

PASSEXPO\_D 00000013 RG 01  
PASSEXPO\_F 00000000 RG 01  
PASSEXPO\_G 00000026 RG 01  
PASSEXPO\_H 0000003A RG 01

+-----+  
! Psect synopsis !  
+-----+

PSECT name	Allocation	PSECT No.	Attributes
ABS	00000000 ( 0.)	00 ( 0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
PASSCODE	0000004E ( 78.)	01 ( 1.)	PIC USR CON REL LCL SHR EXE RD NOWRT NOVEC LONG

+-----+  
! Performance indicators !  
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	10	00:00:00.09	00:00:00.70
Command processing	74	00:00:00.66	00:00:03.46
Pass 1	64	00:00:00.50	00:00:01.97
Symbol table sort	0	00:00:00.00	00:00:00.00
Pass 2	52	00:00:00.41	00:00:01.92
Symbol table output	2	00:00:00.01	00:00:00.01
Psect synopsis output	2	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	206	00:00:01.70	00:00:08.09

The working set limit was 750 pages.  
2491 bytes (5 pages) of virtual memory were used to buffer the intermediate code.  
There were 10 pages of symbol table space allocated to hold 4 non-local and 0 local symbols.  
231 source lines were read in Pass 1, producing 19 object records in Pass 2.  
0 pages of virtual memory were used to define 0 macros.

+-----+  
! Macro library statistics !  
+-----+

Macro library name	Macros defined
_\$255\$DUA28:[SYSLIB]STARLET.MLB;2	0

0 GETS were required to define 0 macros.

There were no errors, warnings or information messages.

MACRO/ENABLE=SUPPRESSION/DISABLE=(GLOBAL,TRACEBACK)/LIS=LIS\$:PASEXPO/OBJ=OBJ\$:PASEXPO MSRC\$:PASEXPO/UPDATE=(ENH\$:PASEXPO)

0294 AH-BT13A-SE  
VAX/VMS V4.0

**DIGITAL EQUIPMENT CORPORATION**  
**CONFIDENTIAL AND PROPRIETARY**